



Manage this device with Digi Remote Manager

DIGI CONNECTPORT X4 FAMILY

Remote M2M networking gateways designed for commercial grade and rugged outdoor applications

Digi ConnectPort® X4 customizable cellular M2M gateways offer a variety of LAN/WAN interface options for end-to-end networking of remote devices. The gateways include comprehensive IP protocols and IPSec VPN support for high-end routing and security. The easy DIA/Python development environment enables custom applications to run locally while interfacing across cellular networks for WAN connectivity to a centralized server.

ConnectPort X4 gateways feature a compact commercial-grade enclosure or an optional outdoors IP66/NEMA 4X enclosure. Interface options include Ethernet, serial and


Zigbee/Rf for flexible connectivity to virtually any remote device.

All Digi ConnectPort X4 gateways feature an end-to-end development environment using comprehensive Digi ESP™ IDE and DIA/Python programming languages. Gain critical insights into your deployed devices and manage your network with **Digi Remote Manager®**. Digi Remote Manager (Digi RM) is a cloud-based solution that facilitates easy setup, mass configuration, maintenance and support for hundreds or even thousands of remote Digi devices.

FEATURES AND BENEFITS

- WAN connectivity via LTE or 3G HSPA+ networks
- Local wireless connectivity through Zigbee
- Local wired connectivity through RS-232/422/485, 2 analog inputs and 2 digital inputs
- Small commercial-grade enclosure or NEMA 4X/IP66 case
- Full routing/IP filtering plus IPsec/SSL VPNs with DES, 3DES or AES encryption
- Easy development environment via DIA and Python scripting as part of Digi ESP IDE
- Support for Modbus/Modbus TCP
- **Digi Remote Manager®** platform for easy setup, mass configuration and management

APPLICATION EXAMPLE



RELATED PRODUCTS



SPECIFICATIONS

DIGI CONNECTPORT® X4

DIGI CONNECTPORT® X4 H

WIRELESS INTERFACES

WWAN**

LTE CAT 1	N/A	Verizon: bands 2,4,14 AT&T & T-Mobile: bands 2,4,5 with 3G/2G fallback
HSPA+ (U9)	850/900/1700 (AWS)/1900/2100 MHz; Transfer rate (max): 5.76 Mbps up, 21 Mbps down	
CONNECTOR	1 or 2 x SMA (center pin - on device: female; on antenna: male)	1 or 2 x SMA (center pin - on device: female; on antenna: male)
SIM SLOTS	2	1
SIM SECURITY	SIM slot cover plate	Internal SIM slot

RF

STANDARD	Zigbee® (2.4 GHz)	
CONNECTOR	1 x RP-SMA (center pin - on device: male; on antenna: female)	

WIRED INTERFACES

SERIAL

PORTS	1	
STANDARD	RS-232	RS-232/422/485 (software selectable)
DTE/DCE	DTE	
SIGNAL SUPPORT	TXD, RXD, RTS, CTS, DTR, DSR and DCD	
FLOW CONTROL	Hardware and software flow control	
COM PORT REDIRECTOR	RealPort®	
THROUGHPUT	Up to 230 Kbps	
CONNECTOR	DB-9 Male	Screw-down terminal block

ETHERNET

PORTS	1	
STANDARD	IEEE 802.3	
PHYSICAL LAYER	10/100 Base-T	
DATA RATE	10/100 Mbps (auto-sensing)	
MODE	Full or half duplex (auto-sensing)	
INTERFACE	Auto MDI/MDIX	
CONNECTOR	RJ-45	

I/O

PORTS	N/A	2 analog and 2 digital
CONNECTOR	N/A	Screw-down terminal block

USB

PORTS	1	
STANDARD	USB 1.1	
SIGNALING	Full-speed	
CONNECTOR	Type A	

SOFTWARE/MANAGEMENT

REMOTE MANAGEMENT	Digi Remote Manager®	
LOCAL MANAGEMENT	Web Interface via HTTP/HTTPS, password access control, IP service port control; CLI via serial port, Telnet, Python scripting (2.4.3); Digi SureLink® "always-on" connection	
SECURITY	SSL tunnels, SSHv2, FIPS 197 (IPsec, HTTPS)	

SPECIFICATIONS

DIGI CONNECTPORT® X4

DIGI CONNECTPORT® X4 H

SOFTWARE/MANAGEMENT (CONTINUED)

NETWORK PROTOCOLS	UDP/TCP, DHCP, SNMPv1/v2	
VPN	IPsec with IKE/ISAKMP; multiple tunnel support; DES, 3DES and up to 256-bit AES encryption; VPN pass-through, GRE forwarding; Simple Certificate Enrollment Protocol (SCEP) for X.509 certificate	
ROUTING	NAT, NAT-T (NAT traversal) VPN tunneling, port forwarding, VPN/GRE pass-through; access control lists (IP filtering), IP pass-through, Virtual Router Redundancy Protocol (VRRP) per RFC 3768	
INDUSTRIAL PROTOCOL SUPPORT	Modbus bridge enables Modbus serial to Modbus/TCP conversion; integrated Python code allows gateway to act as Modbus client/master or Modbus server/slave; functions like an Ethernet to serial bridge, but uses Digi XBee® to transport serial data; handles unique timing issues per Modbus protocol rules; uses Modbus Unit ID to look up IP or mesh MAC address	
REAL-TIME CLOCK	Yes	
MEMORY	16 MB Flash, 32 MB RAM	
POWER		
INPUT	6-30 VDC	100-240 VAC
CONSUMPTION	Idle: 1.5 W, Max: 10.4 W	Approx. 15 W
PROTECTION	4 kV burst (EFT) per-4-4, 2 kV surge per EN61000-4	2 kV burst (EFT) (with included power supply)
CONNECTOR	Locking barrel	Pigtail AC power cord
DC POWER CORD*	Available upon request	N/A
AC POWER SUPPLY*	12 VDC power supply for 0° C to 40° C (32° F to 104° F) included; extended temperature power supply available separately	Internal
BATTERY BACKUP	N/A	
PHYSICAL		
DIMENSIONS (L X W X H)	13.33 cm x 8.50 cm x 2.54 cm (5.25 in x 3.35 in x 1.00 in)	240 mm x 160 mm x 95 mm (9.50 in x 6.25 in x 3.75 in)
WEIGHT	0.20 kg (0.44 lb)	1.41 kg (3.10 lb)
STATUS LEDS	Ethernet status, power, cellular link/activity, signal strength (4 bars), Digi XBee link/activity	Ethernet status, power, cellular link/activity, signal strength (5 bars), Digi XBee link/activity
ENCLOSURE MATERIAL	Industrial (metal)	NEMA 4X
ENCLOSURE RATING	N/A	IP66
MOUNTING	Wall-mount bracket sold separately	4x mounting feet on the unit's flange
ENVIRONMENTAL		
OPERATING TEMPERATURE ***	-30° C to 75° C (-22° F to 167° F)	
STORAGE TEMPERATURE	-40° C to 85° C (-40° F to 185° F)	
RELATIVE HUMIDITY	5% to 95% (non-condensing)	N/A (enclosure is water-tight)
ETHERNET ISOLATION	1500 VAC min per IEEE 802.3/ANSI X3.263	
SERIAL PORT PROTECTION (ESD)	+15 kV Air Gap and +8 kV contact discharge per IEC 1000-4-2	
HAZARDOUS (CLASS 1 DIV 2)	No	No
APPROVALS		
GSM/UMTS	PTCRB, NAPRD.03, GCF-CC, R&TTE, EN 301 511	
CELLULAR CARRIERS	Certified by most major carriers; visit www.digi.com/resources/certifications for latest cellular certifications	
SAFETY	UL 60950, CSA 22.2 No. 60950, EN62368; Class 1 Div 2 (IA model only)	
EMISSIONS/IMMUNITY	CE, FCC Part 15 (Class A), AS/NZS CISPR 22, EN55024, EN55032, Class A	
WARRANTY		
PRODUCT WARRANTY	3-year	

*Optional hardware

**Transfer rates are network operator dependent

***Reduced cellular performance may occur above 60° C (140° F). Standard temperature power supplies may reduce temperature range.

DIGI REMOTE MANAGER®



Digi Remote Manager is the technology platform that brings networks to the next level, allowing networks — and the people who manage them — to work smarter. With Digi Remote Manager you can transform a multitude of dispersed IoT devices into a dynamic, intelligent network. Now you can easily deploy, monitor and diagnose thousands of mission-critical devices from a single point of command — on your desktop, tablet or phone. All the while, its software-defined security diligently safeguards your entire Digi ecosystem.

Learn more at www.digi.com/digi-remote-manager

CAPABILITIES

- Activate, monitor and diagnose your mission-critical devices from a single point of command and control — on your desktop or mobile app
- Schedule key operations — including firmware updates and file management — on a single device or on a group of devices, keeping your network functionality up-to-date and maintaining compliance standards
- Manage edge devices out-of-band via console terminal access
- Keep tabs on device health and connectivity across device deployments of any size
- Create detailed reports and enable real-time alerts for specified conditions
- Integrate device data through open APIs to gain deeper insights and control with third-party applications
- Report and alert on performance statistics, including connection history, signal quality, latency, data usage and packet loss

INFRASTRUCTURE

- Hosted in a commercial-grade cloud server environment that meets SOC 1®, SOC 2® and SOC 3® standards
- Superior availability, operating to 99.9% or greater
- Open APIs available to support application development

SECURITY

- More than 175 security controls in place to protect your data
- Member of the Center for Internet Security® (CIS®)
- Enables compliance with security frameworks like ISO27002, HIPAA, NIST and more
- Earned Skyhigh's CloudTrust™ Program highest rating of Enterprise-Ready

PART NUMBERS	DESCRIPTION
ConnectPort X4 H - Zigbee	
X4H-Z1U-L301-US	ConnectPort X4 H -Digi XBee Zigbee to Ethernet & cellular (LTE)
ConnectPort X4 - Zigbee	
X4-Z11-E-A	ConnectPort X4 - Digi XBee Zigbee to Ethernet
X4-Z11-E-W	ConnectPort X4 - Digi XBee Zigbee to Ethernet (International)
X4-Z1J-U901-W	ConnectPort X4 - Digi XBee Zigbee to Ethernet & cellular (HSPA+) (International)
X4-Z1U-U901-A	ConnectPort X4 - Digi XBee Zigbee to Ethernet & cellular (HSPA+)

PART NUMBERS	DIGI REMOTE MANAGER®
DIGI-RM-STD-1YR	Digi Remote Manager Standard - 1-year subscription
DIGI-RM-PRM-1YR	Digi Remote Manager Premier - 1-year subscription
DIGI-RM-PRM-3YR	Digi Remote Manager Premier - 3-year subscription
DIGI-RM-PRM-5YR	Digi Remote Manager Premier - 5-year subscription

DIGI SERVICE AND SUPPORT / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit www.digi.com/support.

© 1996-2021 Digi International Inc. All rights reserved.
All trademarks are the property of their respective owners.

91001460
G6/521

DIGI INTERNATIONAL WORLDWIDE HQ
877-912-3444 / 952-912-3444 / www.digi.com

DIGI INTERNATIONAL JAPAN
+81-3-5428-0261 / www.digi-intl.co.jp

DIGI INTERNATIONAL GERMANY
+49-89-540-428-0

DIGI INTERNATIONAL SINGAPORE
+65-6213-5380

DIGI INTERNATIONAL CHINA
+86-21-50492199 / www.digi.com.cn

